

015 Green Nozzle Type	bar	flow l/min	Application rates in L/Hectare at 0.5 m spacing					
			8 km/h	10 km/h	12 km/h	14 km/h	16 km/h	18 km/h
GuardianAir™	1.0	0.346	52	42	35	30	26	23
DriftBeta	2.0	0.490	73	59	49	42	37	33
Lo-Drift®	3.0	0.600	90	72	60	51	45	40
VP Flat Fan	4.0	0.693	104	83	69	59	52	46
	5.0	0.775	116	93	77	66	58	52
	6.0	0.849	127	102	85	73	64	57

035 Brown Red Nozzle Type	bar	flow l/min	Application rates in L/Hectare at 0.5 m spacing					
			8 km/h	10 km/h	12 km/h	14 km/h	16 km/h	18 km/h
GuardianAir™	1.0	0.808	121	97	81	69	61	54
VP Flat Fan	2.0	1.143	171	137	114	98	86	76
	3.0	1.400	210	168	140	120	105	93
	4.0	1.616	242	194	162	139	121	108
	5.0	1.807	271	217	181	155	136	120
	6.0	1.980	297	238	198	170	149	132

02 Yellow Nozzle Type	bar	flow l/min	Application rates in L/Hectare at 0.5 m spacing					
			8 km/h	10 km/h	12 km/h	14 km/h	16 km/h	18 km/h
GuardianAir™	1.0	0.462	69	55	46	40	35	31
DriftBeta	2.0	0.653	98	78	65	56	49	44
Lo-Drift®	3.0	0.800	120	96	80	69	60	53
VP Flat Fan	4.0	0.924	139	111	92	79	69	62
GuardianAir Twin™	5.0	1.033	155	124	103	89	77	69
	6.0	1.130	170	136	113	97	85	75

04 Red Nozzle Type	bar	flow l/min	Application rates in L/Hectare at 0.5 m spacing					
			8 km/h	10 km/h	12 km/h	14 km/h	16 km/h	18 km/h
GuardianAir™	1.0	0.924	139	111	92	79	69	62
DriftBeta	2.0	1.306	196	157	131	112	98	87
Lo-Drift®	3.0	1.600	240	192	160	137	120	107
VP Flat Fan	4.0	1.848	277	222	185	158	139	123
GuardianAir Twin™	5.0	2.066	310	248	207	177	155	138
	6.0	2.260	339	271	226	194	170	151

025 Lilac Nozzle Type	bar	flow l/min	Application rates in L/Hectare at 0.5 m spacing					
			8 km/h	10 km/h	12 km/h	14 km/h	16 km/h	18 km/h
GuardianAir™	1.0	0.577	87	69	58	49	43	38
DriftBeta	2.0	0.816	122	98	82	70	61	54
Lo-Drift®	3.0	1.000	150	120	100	86	75	67
VP Flat Fan	4.0	1.155	173	139	115	99	87	77
GuardianAir Twin™	5.0	1.291	194	155	129	111	97	86
	6.0	1.414	212	170	141	121	106	94

05 Brown Nozzle Type	bar	flow l/min	Application rates in L/Hectare at 0.5 m spacing					
			8 km/h	10 km/h	12 km/h	14 km/h	16 km/h	18 km/h
GuardianAir™	1.0	1.155	173	139	115	99	87	77
DriftBeta	2.0	1.633	245	196	163	140	122	109
Lo-Drift®	3.0	2.000	300	240	200	171	150	133
VP Flat Fan	4.0	2.309	346	277	231	198	173	154
GuardianAir Twin™	5.0	2.582	387	310	258	221	194	172
	6.0	2.828	424	339	283	242	212	188

03 Blue Nozzle Type	bar	flow l/min	Application rates in L/Hectare at 0.5 m spacing					
			8 km/h	10 km/h	12 km/h	14 km/h	16 km/h	18 km/h
GuardianAir™	1.0	0.693	104	83	69	59	52	46
DriftBeta	2.0	0.980	147	118	98	84	73	65
Lo-Drift®	3.0	1.200	180	144	120	103	90	80
VP Flat Fan	4.0	1.386	208	166	139	119	104	92
GuardianAir Twin™	5.0	1.549	232	186	155	133	116	103
	6.0	1.700	255	204	170	146	128	113

06 Grey Nozzle Type	bar	flow l/min	Application rates in L/Hectare at 0.5 m spacing					
			8 km/h	10 km/h	12 km/h	14 km/h	16 km/h	18 km/h
DriftBeta	1.0	1.386	208	166	139	119	104	92
Lo-Drift®	2.0	1.960	294	235	196	168	147	131
VP Flat Fan	3.0	2.400	360	288	240	206	180	160
GuardianAir Twin™	4.0	2.771	416	333	277	238	208	185
	5.0	3.098	465	372	310	266	232	207
	6.0	3.393	509	407	339	337	295	262